

R.125 & R.125SS



Stainless Steel



Steel



AN EXCELLENT PARTNER FOR YOUR BACK AND YOUR HEALTH

Discover our range of **R.125** forklifts, suitable for the needs of small and medium-sized businesses, as well as demanding industrial environments. The standard R.125 offers a compact, robust design and exceptional maneuverability with its front swivel wheels. It can safely lift loads of up to 125 kg to a height of 239 cm. Equipped with overload protection, a safety clutch, and soft start, it facilitates safe handling. Our extensive catalog of standard or modifiable tools allows for lifting a variety of loads, from coils to pallets.

As for the R.125 SS in Stainless Steel, it is specially designed for demanding industrial environments such as the food industry and the medical sector. With an IP 65 certification, it withstands thorough cleaning, moisture, and cold areas. It adapts to a wide range of loads and offers automatic positioning for added ergonomics.

The R.125 is delivered with AGM batteries (24 V ; 9 Ah) as standard.



Lift



Move

Features

DESCRIPTION	
CMU	125 Kg (S/M) - 110 Kg (L)
Material	Steel Stainless Steel
Command type	Remote control
Battery indicator	On the remote control unit
Battery type	2 AGM (Tot : 24 V - 9 Ah)
Charger	External - 230 V - 50/60 Hz
Number of cycles	80 to 150 cycles
Recharge time	7,5 hours (100%)



MADE IN FRANCE

Contact us :
02 28 21 73 95
info@reglift.fr

Visit our website:
www.reglift.com

REGLIFT
9 rue de la Fontaine Grillée
44690 La Haie Fouassière

General view


Material

- Steel: IP44
- Stainless steel: IP65

Tool holder

- Home a wide range of manual and power tools
- Quick change system
- Automatic level option
- Position encoder

Braking system



- Central braking

Wheels



- Fixed and free wheels at the front and the rear
- ESD

Variable mast sizes

- **L**
 - Mast size : 2390 mm
 - Elevation stroke : 2050 mm
- **M**
 - Mast size : 1940 mm
 - Elevation stroke : 1600 mm
- **S**
 - Mast size : 1560 mm
 - Elevation stroke : 1220 mm

Handle

- Ergonomic handle: Ergo Control
- Fixed or detachable remote control
- 8 different configurations

Battery options


- Interchangeable batteries
- Lithium battery
- Charger storage case

Legs

- 2 leg configurations
- Different lengths and widths available
- Widening the footings



Examples of tools




Double boom




Jib crane



Platform with rollers



Narrow fork



Electric clamp with rotation system

