

Oilfield Hoist Block Model No. 8-591



Main Features

- Manufactured with the highest quality alloy steel
- Available from 4 tonnes to 30 tonnes, for wire rope sizes 8mm to 20mm
- Part number, wire rope size and working load limit are marked on each block
- Permanent batch codes link to test certificates for easy traceability
- Supplied with sealed tapered bearings for extended product life and faster line speeds
- Safety factor 4:1
- Manufactured by an API Q1 certified facility



Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Technical Data

| Product Code | Sheave Dia (inch) | Bearing Type | Wire Rope Size (mm) | Capacity (tonnes)* | Net Weight | |
|---------------|-------------------|--------------|---------------------|--------------------|------------|------|
| | | | | | Ibs | kg |
| 8-591-0408 | 8 | TB | 10-13 | 4.0 | 35 | 16.0 |
| 8-591-0810-13 | 10 | TB | 10-13 | 8.0 | 55 | 25.0 |
| 8-591-0810-15 | 10 | TB | 13-15 | 8.0 | 55 | 25.0 |
| 8-591-1214-19 | 14 | TB | 19 | 12.0 | 95 | 43.0 |

*Minimum Ultimate Load is 4 times the Working Load Limit
TB = Tapered Bearing

Other sizes available - please ask for details.

Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.